

BaseKnit 1308 halffinger

AERO®



EN 388
X132X

CE
CAT. II



SPECIFICATION

KNITTED FABRIC	The AERO® BaseKnit nylon knit provides perfect dexterity. This knitted fabric is very often used as an insert in rubber and plastic gloves for increased wearing comfort. Thanks to a low occurrence of loose fibres and textile dust, the knitted fabric is often used in a clean environment.
UNDERLAY FINENESS	Fine 13
SIZES	S/6, M/7, L/8
CHARACTERISTICS	Comfortable inserts for gloves and fingerless gloves. For special handling.
PROTECTION	Cutting
USE	Automotive industry, normal handling, assembly, delicate work, electronic industry, finishing works, packaging technology, laboratory and pharmaceutical activities, food industry



EVALUATION (PALM SIDE)

Breathability	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Moisture absorption	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Knitted fabric softness	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wearing comfort level	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

MECHANICAL PROTECTION

Abrasion resistance (cycles)	100	500	2000	8000		
Based on the number of cycles necessary to tear through a sample of the glove						
Resistance to cutting (index)	1,2	2,5	5,0	10,0	20,0	
Based on the number of blade cycles necessary to cut through a sample at a constant speed						
Resistance to tearing (Newton)	10	25	50	75		
Based on the force necessary to tear the sample						
Resistance to puncturing (Newton)	20	60	100	150		
Based on the force necessary to puncture the sample with a standard-sized point						
Resistance to cutting (Newton)	2	5	10	15	22	30
TDM resistance to cutting according to EN 388:2016 ISO 13997						

PACKING DETAILS


Size	Carton size Carton volume Carton weight	Packaging of individual pair	Number of pairs in package	Number of pairs in carton	Barcode 1 pair	Barcode carton
S/6	53 x 22 x 38 cm 0.044 m ³ 5.7 kg	NO	12	300	 8 594182 288681	 8 594182 288698
M/7	53 x 22 x 38 cm 0.044 m ³ 6.2 kg	NO	12	300	 8 594182 288704	 8 594182 288711
L/8	53 x 26 x 38 cm 0.052 m ³ 6.4 kg	NO	12	300	 8 594182 288728	 8 594182 288735


STORAGE

The products should be stored in dry and well-ventilated areas. Excessive air humidity, temperature or intensive light may affect quality of the gloves. The supplier bears no responsibility for damage incurred due to the afore-mentioned causes.

MANUFACTURER'S RECOMMENDATION

Use the gloves according to the assessed risks, in accordance with the appropriate norms. The content of the appropriate norms will be provided to you, on request, by an authorized distributor of the AERO and WORKSHOP brands.

 Sign of conformity with harmonised European CAT norms. II. Gloves for work and protection against medium risks, e.g. in the case of gloves for general handling, good protection against cutting, puncturing and abrasion must be subject to independent testing, and must be certified by an official body.

 The pictograms on the left indicate that the user must read the information leaflet (in every package) before using the gloves.