

SoftKnit 1339 optimal

AERO®



EN 388
1131X

CE
CAT. II



SPECIFICATION

KNITTED FABRIC	The AERO SoftKnit nylon knit provides truly first-rate dexterity, and better abrasion resistance and durability than cotton material. The knitted fabric's medium square weight increases mechanical protection and durability, and also increases protection against the formation of fingerprints (product protection).
UNDERLAY FINENESS	13G
SIZES	XS/5, S/6, M/7, L/8, XL/9, XXL/10, 3XL/11
CHARACTERISTICS	Gloves which protect against impurities. They do not leave fingerprints.
PROTECTION	Cutting.
USE	Automotive industry, normal handling, assembly, delicate work, finishing works, packaging technology, agriculture and gardening.



TECHNICAL CERTIFICATE AND INSTRUCTIONS

EVALUATION (PALM SIDE)

Breathability	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Moisture absorption	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Knitted fabric softness	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wearing comfort level	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

MECHANICAL PROTECTION

Abrasion resistance (cycles) 100 500 2000 8000

Based on the number of cycles necessary to tear through a sample of the glove

Resistance to cutting (index) 1,2 2,5 5,0 10,0 20,0

Based on the number of blade cycles necessary to cut through a sample at a constant speed

Resistance to tearing (Newton) 10 25 50 75

Based on the force necessary to tear the sample















Resistance to puncturing (Newton) 20 60 100 150

Based on the force necessary to puncture the sample with a standard-sized point

Resistance to cutting (Newton) 2 5 10 15 22 30

TDM resistance to cutting according to EN 388:2016 ISO 13997

PACKING DETAILS


Size	Carton size Carton volume Carton weight	Packaging of individual pair	Number of pairs in package	Number of pairs in carton	Barcode 1 pair	Barcode carton
XS/5	53 x 26 x 36,5 cm 0,050 m ³ 5,93 kg	NO	12	240	 8 594182 289329	 8 594182 289336
S/6	53 x 26 x 36,5 cm 0,050 m ³ 6,17 kg	NO	12	240	 8 594182 289367	 8 594182 289374
M/7	53 x 26 x 36,5 cm 0,050 m ³ 7 kg	NO	12	240	 8 594182 289305	 8 594182 289312
L/8	53 x 26 x 36,5 cm 0,050 m ³ 8 kg	NO	12	240	 8 594182 289343	 8 594182 289350
XL/9	53 x 26 x 36,5 cm 0,050 m ³ 8 kg	NO	12	240	 8 594182 289381	 8 594182 289398
XXL/10	53 x 26 x 36,5 cm 0,050 m ³ 8,5 kg	NO	12	240	 8 594182 289404	 8 594182 289411
3XL/11	53 x 26 x 36,5 cm 0,050 m ³ 8,75 kg	NO	12	240	 8 595683 008563	 8 595683 008570


STORAGE

The products should be stored in dry and well-ventilated areas. Excessive air humidity, temperature or intensive light may affect quality of the gloves. The supplier bears no responsibility for damage incurred due to the afore-mentioned causes.

MANUFACTURER'S RECOMMENDATION

Use the gloves according to the assessed risks, in accordance with the appropriate norms. The content of the appropriate norms will be provided to you, on request, by an authorized distributor of the AERO and WORKSHOP brands.

 Sign of conformity with harmonised European CAT norms. II. Gloves for work and protection against medium risks, e.g. in the case of gloves for general handling, good protection against cutting, puncturing and abrasion must be subject to independent testing, and must be certified by an official body.

 The pictograms on the left indicate that the user must read the information leaflet (in every package) before using the gloves.