

# BaseCut 1655 superknit cut F

NEW 06/2020

# AERO®



EN 388  
3X43F



## SPECIFICATION

KNITTED FABRIC	Hi-Tech superknit fibre without added glass or steel fibres
SIZES	M/7, L/8, XL/9, XXL/10
CHARACTERISTICS	Gloves which protect against cutting
PROTECTION	Cutting, tearing
USE	Glass production, automotive industry, food industry, engineering, construction, civil engineering, work with sharp objects and work which involves a risk of cuts, logistics and warehousing



## EVALUATION (PALM SIDE)

Breathability	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Knitted fabric softness	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wearing comfort level	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

## MECHANICAL PROTECTION

Abrasion resistance (cycles)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
------------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Based on the number of cycles necessary to tear through a sample of the glove

Resistance to cutting (index)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
-------------------------------	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Based on the number of blade cycles necessary to cut through a sample at a constant speed

Resistance to tearing (Newton)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--------------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Based on the force necessary to tear the sample













Resistance to puncturing (Newton)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
-----------------------------------	--------------------------	--------------------------	--------------------------	--------------------------

Based on the force necessary to puncture the sample with a standard-sized point

Resistance to cutting (Newton)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
--------------------------------	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------	--------------------------

TDM resistance to cutting according to EN 388:2016 ISO 13997

## PACKING DETAILS


Size	Carton size Carton volume Carton weight	Packaging of individual pair	Number of pairs in package	Number of pairs in carton	Barcode 1 pair	Barcode carton
S/6	65 x 28 x 22 cm 0.04 m <sup>3</sup> 8.5 kg	YES	12	120	 8 595683 003896	 8 595683 003902
M/7	65 x 28 x 22 cm 0.04 m <sup>3</sup> 8.5 kg	YES	12	120	 8 595683 003919	 8 595683 003926
L/8	65 x 28 x 22 cm 0.04 m <sup>3</sup> 9.4 kg	YES	12	120	 8 595683 003933	 8 595683 003940
XL/9	65 x 28 x 22 cm 0.04 m <sup>3</sup> 9.7 kg	YES	12	120	 8 595683 003957	 8 595683 003964
XXL/10	65 x 28 x 22 cm 0.04 m <sup>3</sup> 10 kg	YES	12	120	 8 595683 003971	 8 595683 003988
3XL/11	65 x 28 x 22 cm 0.04 m <sup>3</sup> 10 kg	YES	12	120	 8 595683 003995	 8 595683 004008


## STORAGE

The products should be stored in dry and well-ventilated areas. Excessive air humidity, temperature or intensive light may affect quality of the gloves. The supplier bears no responsibility for damage incurred due to the afore-mentioned causes.

## MANUFACTURER'S RECOMMENDATION

Use the gloves according to the assessed risks, in accordance with the appropriate norms. The content of the appropriate norms will be provided to you, on request, by an authorized distributor of the AERO and WORKSHOP brands.

 Sign of conformity with harmonised European CAT norms. II. Gloves for work and protection against medium risks, e.g. in the case of gloves for general handling, good protection against cutting, puncturing and abrasion must be subject to independent testing, and must be certified by an official body.

 The pictograms on the left indicate that the user must read the information leaflet (in every package) before using the gloves.