PurtSkin 1673-1 superknit cut C white

AERO

IN PREPARATION









SPECIFICATION

COATING	The AERO® PurtSkin coating is a special thin polyurethane coating which provides excellent grip whether dry or wet, as well as first-class dexterity. The AERO® PurtSkin coating makes gloves more durable and flexible, as well as offering excellent sensitivity. The coating is designed to increase resistance to abrasion and tearing, and its breathable structure offers maximum comfort for the reduction of hand fatigue.	
KNITTED FABRIC	Super fine Hi-Tech superknit without added glass or steel fibres	
UNDERLAY FINENESS	Fine 13	
SIZES	S/6, M/7, L/8, XL/9, XXL/10, 3XL/11	
CHARACTERISTICS	Gloves which protect against cutting. With a layer for better grip and protection.	
PROTECTION	Abrasion, cutting, tearing, puncturing	
USE	Glass production, automotive industry, engineering, construc- tion, civil engineering, work with sharp objects and work which involves a risk of cuts and abrasion, logistics and warehousing	



Grip when dry	
Grip when wet	
Slip-resistant treatment for contact with oil	
Resistance to permeation by oil	
Resistance to permeation by H ₂ O solution	
Breathability	
Knitted fabric softness	
Wearing comfort level	

MECHANICAL PROTECTION

41 / 1 \	100	500		00	0000	
Abrasion resistance (cycles)	100	500	20	00	8000	
Based on the number of cycles necessary to tear through a sample of the glove						
, ,						
Resistance to cutting (index)	1,2	2,5	5,	0	10,0	20,0
Based on the number of blade cycles necessary to cut through a sample at a constant speed						
Resistance to tearing (Newton)	10	25	5	0	75	
Based on the force necessary to tear the sample						
D 1						
Resistance to puncturing (Newton)	20	60	10	00	150	
Based on the force necessary to puncture the sample with a standard-sized point						
Resistance to cutting (Newton)	2	5	10	15	22	30
TDM resistance to cutting according to EN 388:2016 ISO 13997						





PurtSkin 1673-1 superknit cut C white



PACKING DETAILS

Size	Carton size Carton volume Carton weight	Packaging of individual pair	Number of pairs in package	Number of pairs in carton	Barcode 1 pair	Barcode carton
S/6	55 x 26 x 42 cm 0.06 m³ 11.4 kg	YES	12	240	8 595683 001120	8 595683 001137
M/7	55 x 26 x 42 cm 0.06 m ³ 11.7 kg	YES	12	240	8 595683 001144	8 595683 001151
L/8	55 x 26 x 42 cm 0.06 m³ 13.2 kg	YES	12	240	8 595683 001168	8 595683 001175
XL/9	57 x 29 x 46 cm 0.076 m ³ 14 kg	YES	12	240	8 595683 001182	8 595683 001199
XXL/10	57 x 29 x 46 cm 0.076 m³ 14.2 kg	YES	12	240	8 594182 283457	8 595683 001205
3XL/11	57 x 29 x 46 cm 0.076 m³ 14.5 kg	YES	12	240	8 595683 001212	8 595683 001229

STORAGE

The products should be stored in dry and well-ventilated areas. Excessive air humidity, temperature or intensive light may affect quality of the gloves. The supplier bears no responsibility for damage incurred due to the afore-mentioned causes.

MANUFACTURER'S RECOMMENDATION

Use the gloves according to the assessed risks, in accordance with the appropriate norms. The content of the appropriate norms will be provided to you, on request, by an authorized distributor of the AERO and WORKSHOP brands.



€ Sign of conformity with harmonised European CAT norms. II. Gloves for work and protection against medium risks, e.g. in the case of gloves for general handling, good protection against cutting, puncturing and abrasion must be subject to independent testing, and must be certified by an official body.



The pictograms on the left indicate that the user must read the information leaflet (in every package) before using the gloves.