PurtSkin 1697 suprathin













SPECIFICATION

offors maximum comfort for the footstall of flatte ranges.	COATING	The AERO® PurtSkin coating is a special thin polyurethane coating which provides excellent grip whether dry or wet, as well as first-class dexterity. The AERO® PurtSkin coating makes gloves more durable and flexible, as well as offering excellent sensitivity. The coating is designed to increase resistance to abrasion and tearing, and its breathable structure affers maximum comfort for the reduction of hand fatigue.
		offers maximum comfort for the reduction of hand fatigue.

KNITTED FABRIC	Nylon
UNDERLAY FINENESS	Exceptionally fine 18
SIZES	S/6, M/7, L/8, XL/9, XXL/10
CHARACTERISTICS	Gloves which protect against impurities. With a layer for better grip and protection.
PROTECTION	Abrasion, tearing
USE	Automotive industry, engineering, normal handling, transportation, assembly, assembly and repair works, delicate work, electronic industry, finishing works, packaging technology




Grip when dry		
Grip when wet		
Slip-resistant treatment for contact with oil		
Resistance to permeation by oil		
Resistance to permeation by H ₂ O solution		
Breathability		
Knitted fabric softness		
Wearing comfort level		

MECHANICAL PROTECTION

TDM resistance to cutting according to EN 388:2016 ISO 13997

Abrasion resistance (cycles)	100	500	200	00	8000	
Based on the number of cycles necessary to tear through a sample of the glove						
Resistance to cutting (index)	1,2	2,5	5,0)	10,0	20,0
Based on the number of blade cycles necessary to cut through a sample at a constant speed						
Resistance to tearing (Newton)	10	25	50)	75	
Based on the force necessary to tear the sample						
Resistance to puncturing (Newton)	20	60	10	0	150	
Based on the force necessary to puncture the sample with a standard-sized point						
Resistance to cutting (Newton)	2	5	10	15	22	30





PurtSkin 1697 suprathin



PACKING DETAILS

Size	Carton size Carton volume Carton weight	Packaging of individual pair	Number of pairs in package	Number of pairs in carton	Barcode 1 pair	Barcode carton
S/6	60 x 25 x 34 cm 0.051 m³ 4.2 kg	NO	12	240	8 595683 002349	8 595683 002356
M/7	60 x 25 x 34 cm 0.051 m³ 4.5 kg	NO	12	240	8 595683 002363	8 595683 002370
L/8	60 x 25 x 34 cm 0.051 m³ 4.9 kg	NO	12	240	8 595683 002387	8 595683 002394
XL/9	60 x 25 x 34 cm 0.051 m³ 5.4 kg	NO	12	240	8 594182 280234	8 595683 002400
XXL/10	60 x 25 x 34 cm 0.051 m³ 5.9 kg	NO	12	240	8 594182 280241	8 595683 002417

STORAGE

The products should be stored in dry and well-ventilated areas. Excessive air humidity, temperature or intensive light may affect quality of the gloves. The supplier bears no responsibility for damage incurred due to the afore-mentioned causes.

MANUFACTURER'S RECOMMENDATION

Use the gloves according to the assessed risks, in accordance with the appropriate norms. The content of the appropriate norms will be provided to you, on request, by an authorized distributor of the AERO and WORKSHOP brands.



€ Sign of conformity with harmonised European CAT norms. II. Gloves for work and protection against medium risks, e.g. in the case of gloves for general handling, good protection against cutting, puncturing and abrasion must be subject to independent testing, and must be certified by an official body.



The pictograms on the left indicate that the user must read the information leaflet (in every package) before using the gloves.