

BaseCut 1746 sleeve 43 cut C premium

AERO®



SPECIFICATION

KNITTED FABRIC	BaseCut, made from Hi-Tech fibres.
SIZES	UNI
SLEEVE LENGTH	43 cm
CHARACTERISTICS	Arm sleeve which protects against cutting. The fluorescent colour ensures high user visibility. The arm sleeve is perfectly flexible, thanks to an innovative material composition which contains spandex. The Velcro in the top part fixes the arm perfectly.
PROTECTION	Abrasion, cutting, tearing, contact heat up to 100°C
USE	Automotive industry, engineering, construction, normal handling, transportation, work with tools, assembly, delicate work, repair works

MECHANICAL PROTECTION

Abrasion resistance (cycles)

100	500	2000	8000
-----	-----	------	------

Based on the number of cycles necessary to tear through a sample of the glove

Resistance to cutting (index)

1,2	2,5	5,0	10,0	20,0
-----	-----	-----	------	------

Based on the number of blade cycles necessary to cut through a sample at a constant speed

Resistance to tearing (Newton)

10	25	50	75
----	----	----	----

Based on the force necessary to tear the sample

Resistance to puncturing (Newton)

20	60	100	150
----	----	-----	-----

Based on the force necessary to puncture the sample with a standard-sized point

Resistance to cutting (Newton)

2	5	10	15	22	30
---	---	----	----	----	----

TDM resistance to cutting according to EN 388:2016 ISO 13997

HEAT RESISTANCE

Resistance to contact heat



100 °C > 15 s	250 °C > 15 s	350 °C > 15 s	500 °C > 15 s
---------------	---------------	---------------	---------------

According to the ratio of the temperature in °C to the time limit



TECHNICAL CERTIFICATE AND INSTRUCTIONS

PACKING DETAILS

Size	Carton size Carton volume Carton weight	Packaging of individual pair	Number of pairs in package	Number of pairs in carton	Barcode 1 pair	Barcode carton
UNI	62 x 44 x 26 cm 0.071 m ³ 14.8 kg	YES	6	120	 8 594182 285352	 8 594182 285369


STORAGE

The products should be stored in dry and well-ventilated areas. Excessive air humidity, temperature or intensive light may affect quality of the gloves. The supplier bears no responsibility for damage incurred due to the afore-mentioned causes.

MANUFACTURER'S RECOMMENDATION

Use the gloves according to the assessed risks, in accordance with the appropriate norms. The content of the appropriate norms will be provided to you, on request, by an authorized distributor of the AERO and WORKSHOP brands.

CE
CAT. II Sign of conformity with harmonised European CAT norms. II. Gloves for work and protection against medium risks, e.g. in the case of gloves for general handling, good protection against cutting, puncturing and abrasion must be subject to independent testing, and must be certified by an official body.

 The pictograms on the left indicate that the user must read the information leaflet (in every package) before using the gloves.