

PurtSkin 1748 black

AERO®



EN 388
4231X

CE
CAT. II




SPECIFICATION

COATING	The AERO® PurtSkin coating is a special thin polyurethane coating which provides excellent grip whether dry or wet, as well as first-class dexterity. The AERO® PurtSkin coating makes gloves more durable and flexible, as well as offering excellent sensitivity. The coating is designed to increase resistance to abrasion and tearing, and its breathable structure offers maximum comfort for the reduction of hand fatigue.
KNITTED FABRIC	The fine nylon (PA) underlay provides perfect dexterity and natural sensitivity
UNDERLAY FINENESS	Fine 13
SIZES	S/6, M/7, L/8, XL/9, XXL/10
CHARACTERISTICS	Gloves which protect against impurities. With a layer for better grip and protection.
PROTECTION	Abrasion, cutting
USE	Automotive industry, engineering, normal handling, transportation, assembly, assembly and repair works, delicate work, electronic industry, finishing works, packaging technology



EVALUATION (PALM SIDE)











Grip when dry	<div></div> <div></div> <div></div> <div></div> <div></div> <div></div>
Grip when wet	<div></div> <div></div> <div></div> <div></div> <div></div> <div></div>
Slip-resistant treatment for contact with oil	<div></div> <div></div> <div></div> <div></div> <div></div> <div></div>
Resistance to permeation by oil	<div></div> <div></div> <div></div> <div></div> <div></div> <div></div>
Resistance to permeation by H ₂ O solution	<div></div> <div></div> <div></div> <div></div> <div></div> <div></div>
Breathability	<div></div> <div></div> <div></div> <div></div> <div></div> <div></div>
Knitted fabric softness	<div></div> <div></div> <div></div> <div></div> <div></div> <div></div>
Wearing comfort level	<div></div> <div></div> <div></div> <div></div> <div></div> <div></div>



MECHANICAL PROTECTION

Abrasion resistance (cycles)	100	500	2000	8000		
Based on the number of cycles necessary to tear through a sample of the glove						
Resistance to cutting (index)	1,2	2,5	5,0	10,0	20,0	
Based on the number of blade cycles necessary to cut through a sample at a constant speed						
Resistance to tearing (Newton)	10	25	50	75		
Based on the force necessary to tear the sample						
Resistance to puncturing (Newton)	20	60	100	150		
Based on the force necessary to puncture the sample with a standard-sized point						
Resistance to cutting (Newton)	2	5	10	15	22	30
TDM resistance to cutting according to EN 388:2016 ISO 13997						

PACKING DETAILS

Size	Carton size Carton volume Carton weight	Packaging of individual pair	Number of pairs in package	Number of pairs in carton	Barcode 1 pair	Barcode carton
S/6	53 x 26 x 37 cm 0.050 m ³ 6.5 kg	YES	12	240	 8 594182 287820	 8 594182 287837
M/7	53 x 26 x 37 cm 0.050 m ³ 6.5 kg	YES	12	240	 8 594182 287844	 8 594182 287851
L/8	53 x 26 x 37 cm 0.050 m ³ 7.2 kg	YES	12	240	 8 594182 287868	 8 594182 287875
XL/9	53 x 26 x 37 cm 0.050 m ³ 7.2 kg	YES	12	240	 8 594182 287882	 8 594182 287899
XXL/10	53 x 26 x 37 cm 0.050 m ³ 7.2 kg	YES	12	240	 8 594182 287905	 8 594182 287912


STORAGE

The products should be stored in dry and well-ventilated areas. Excessive air humidity, temperature or intensive light may affect quality of the gloves. The supplier bears no responsibility for damage incurred due to the afore-mentioned causes.

MANUFACTURER'S RECOMMENDATION

Use the gloves according to the assessed risks, in accordance with the appropriate norms. The content of the appropriate norms will be provided to you, on request, by an authorized distributor of the AERO and WORKSHOP brands.

CE
CAT. II Sign of conformity with harmonised European CAT norms. II. Gloves for work and protection against medium risks, e.g. in the case of gloves for general handling, good protection against cutting, puncturing and abrasion must be subject to independent testing, and must be certified by an official body.

 The pictograms on the left indicate that the user must read the information leaflet (in every package) before using the gloves.