

BaseCut 1995 simplex cut C

AERO®



EN 388
4X42C

CE
CAT. II



SPECIFICATION

KNITTED FABRIC	BaseCut knit made from Hi-Tech fibres. The added Lycra and nylon fibres increase dexterity and comfort.
SIZES	S/6, M/7, L/8, XL/9, XXL/10
CHARACTERISTICS	Gloves which protect against cutting
PROTECTION	Abrasion, cutting, tearing
USE	Glass production, automotive industry, engineering, construction, civil engineering, work with sharp objects and work which involves a risk of cuts and abrasion, logistics and warehousing













EVALUATION (PALM SIDE)

Breathability	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Knitted fabric softness	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wearing comfort level	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

MECHANICAL PROTECTION

Abrasion resistance (cycles)	100	500	2000	8000		
Based on the number of cycles necessary to tear through a sample of the glove						
Resistance to cutting (index)	1,2	2,5	5,0	10,0	20,0	
Based on the number of blade cycles necessary to cut through a sample at a constant speed						
Resistance to tearing (Newton)	10	25	50	75		
Based on the force necessary to tear the sample						
Resistance to puncturing (Newton)	20	60	100	150		
Based on the force necessary to puncture the sample with a standard-sized point						
Resistance to cutting (Newton)	2	5	10	15	22	30
TDM resistance to cutting according to EN 388:2016 ISO 13997						

PACKING DETAILS


Size	Carton size Carton volume Carton weight	Packaging of individual pair	Number of pairs in package	Number of pairs in carton	Barcode 1 pair	Barcode carton
S/6	51 x 26 x 23 cm 0,030 m ³ 6 kg	YES	12	240	 8 594182 286304	 8 594182 286311
M/7	51 x 26 x 23 cm 0,030 m ³ 6,5 kg	YES	12	240	 8 594182 286328	 8 594182 286335
L/8	51 x 26 x 23 cm 0,030 m ³ 7 kg	YES	12	240	 8 594182 286342	 8 594182 286359
XL/9	51 x 26 x 23 cm 0,030 m ³ 7,5 kg	YES	12	240	 8 594182 286366	 8 594182 286373
XXL/10	51 x 26 x 23 cm 0,030 m ³ 8 kg	YES	12	240	 8 594182 286380	 8 594182 286397


STORAGE

The products should be stored in dry and well-ventilated areas. Excessive air humidity, temperature or intensive light may affect quality of the gloves. The supplier bears no responsibility for damage incurred due to the afore-mentioned causes.

MANUFACTURER'S RECOMMENDATION

Use the gloves according to the assessed risks, in accordance with the appropriate norms. The content of the appropriate norms will be provided to you, on request, by an authorized distributor of the AERO and WORKSHOP brands.

 **CAT. II** Sign of conformity with harmonised European CAT norms. II. Gloves for work and protection against medium risks, e.g. in the case of gloves for general handling, good protection against cutting, puncturing and abrasion must be subject to independent testing, and must be certified by an official body.

 The pictograms on the left indicate that the user must read the information leaflet (in every package) before using the gloves.